

DESTROYIT® 5009

Conveyor-fed shredder features a sheet capacity of over 600 and a 79 gallon shred volume. An optional exit conveyor belt system increases shred capacity by transporting shredded material to an external container. Centralized oiler provides lubrication for the cutting shafts.



A SIMPLIFIED CONTROLS
Operation is controlled by an ergonomic control panel. Optical indicators display operational status.

B ROBUST CUTTING UNIT
Industrial, tempered steel cutting head will easily destroy hardbound documents including full sized 3-ring binders.

C CENTRALIZED OILER
Conveniently located centralized oiler provides quick and easy lubrication of the cutting shafts.

D MOBILE SHRED BIN
79 gallon shred bin is mounted on heavy duty casters for easy mobility. Shredder stops automatically when door is opened.

*Super micro-cut shafts are covered by a 1 year warranty.



www.mbmcorp.com
843-552-2700



DESTROYIT® 5009

Extra large feed table with powered conveyor belt feed system. Convenient centralized oiler for lubrication of the cutting shafts. Electronically controlled safety guard. Safety lock and key, main switch, and emergency stop button. Automatic power cutoff when cabinet is opened or shred bag is full. Automatic reverse and power cutoff when overfed. Thermal switch prevents overheating. Push button control panel with optical indicators to show operational status. 2 automatic speed modes: POWER for bulk feeding large quantities of paper and SPEED for high speed shredding of lesser amounts. Soft metal resistant, hardened steel cutting shafts take CDs / DVDs, hardbound documents, and 3ring binders. Dual 3 phase motors (24 maximum horsepower) rated for continuous operation. Fully enclosed gear box housing. Mounted on heavy duty casters. Rear opening cabinet door and mobile shred bin with bag mounting frame for easy replacement of shred bags. Optional accessories: modular exit conveyor belt system and additional shred bins.



Security level P-2 .35 x 1.5"-3" cross-cut (8 x 40-80 mm)
Sheet capacity 600 - 700*

Security level P-3 .25" x 2" cross-cut (6 x 50 mm)
Sheet capacity 300 - 400*


* Sheet Capacity is based on 70 gsm paper, and are normally only achievable in ideal situations, so heavier duty paper will shred less sheets. In many cases the capacities quoted are theoretical as conditions vary and are dependent on operator usage, age and condition of machines, how regularly cutters are oiled, type and quality of paper etc. so realistic throughputs can be as low as half that of the theoretical capacities quoted.

Specifications:

Shred volume	79 gallons
Feed opening	20"
Electrical requirements	220 volts, 3 phase ¹
Maximum horsepower	24
Dimensions (D x W x H)	85.5" x 40.7" x 67.5" ²
Shipping weight	3,080 lbs

¹ 50 amp. dedicated line required.

² depth with modular exit conveyor belt system is 121"



www.mbmcorp.com
 843-552-2700

