




The features you deserve.



SPS Safety Protection System includes: Transparent Safety Shield, automatic reverse and stop, power cut-off when the cabinet is opened or the bin is full, electronic door protection, and double protection against overheating.

- 100% German-made with the highest safety standards. ✓
- Best warranty in the industry. ✓
- A return rate of less than 1%. ✓
- First shredder to be awarded the "Blue Angel" certification. ✓
- Promotes free trade through the Trade Agreement Act. ✓
- Zero Energy Consumption is standard with every model. ✓
- Superior customer and technical service. ✓
- Same-day shipping. ✓

**Super micro-cut and High Capacity shafts are covered by a one-year limited warranty.*

DESTROYIT



versatility
shred receipts to office paper
to cds/dvds and more



sheet capacity
5 to 700 sheets



throat opening
8 3/4" to 20"

range of options
over 30 models



security levels
p-2 to p-7



mobility
lightweight models and
casters for mobility




The essential security measure.

Shredding documents before they leave the building is the only way to be sure they are properly destroyed. Using a shred service is relinquishing control of your data security program. A stranger is put in possession of your sensitive materials.

If you use a shredding service, documents are leaving the building intact, in the hands of strangers. The false sense of security they provide is accompanied by a never-ending expense which will only increase over time. That's why shredding at the source with Destroyit shredders should be the foundation of every data security program.

DESTROYIT

PAPER SHREDDERS



3134 Industry Drive
North Charleston, SC 29418
843-552-2700
www.mbmcorp.com



945B Southgate Drive
Guelph, ON N1L 0B9
800-387-2528
www.ideal-mbm.com



843-552-2700
www.mbmcorp.com

DESKSIDE

Deskside shredders put effective data security right at your side. Unlike cheaper brands, they are built with the highest quality materials and construction standards to provide years of dependable service.

Model	Strip width / particle size	Feed opening	Sheet capacity ¹	Security level	Shredding capabilities (non-paper)	Shred speed, ft. / min.	Shred volume, gallons	Electrical requirements, volts	Maximum horsepower	Automatic oil injection / SSC ² / ECC ³	Dimensions (D x W x H)	Shipping weight
2265 cross-cut	.125" x 1" (3 x 25 mm)	8.75"	5-6	P-4		12	5	115	1/5 (.15 kw)	-	8.7" x 13.5" x 21"	28 lbs.
2445 cross-cut	.187" x 1.5" (4 x 40 mm)	9.5"	11-13	P-4		14	9	115	1/2 (.39 kw)	SSC	11.7" x 15.5" x 28.7"	53 lbs.
2445 cross-cut	.093" x .625" (2 x 15 mm)	9.5"	6-8	P-5		14	9	115	1/2 (.39 kw)	SSC	11.7" x 15.5" x 28.7"	53 lbs.
2445 super micro-cut	.031" x .187" (.8 x 5 mm)	9.5"	5-7	P-7	-	14	9	115	1/2 (.39 kw)	SSC	11.7" x 15.5" x 25"	53 lbs.
2465 strip-cut	.187" (4 mm)	9.5"	19-22	P-2		27	9	115	3/4 (.58 kw)	SSC	11.5" x 15.5" x 25"	58 lbs.
2465 cross-cut	.187" x 1.5" (4 x 40 mm)	9.5"	13-15	P-4		27	9	115	3/4 (.58 kw)	SSC	11.5" x 15.5" x 25"	58 lbs.
2465 cross-cut	.093" x .625" (2 x 15 mm)	9.5"	9-11	P-5		27	9	115	3/4 (.58 kw)	SSC	11.5" x 15.5" x 25"	58 lbs.

CENTRALIZED OFFICE

Centralized Office models are commercial grade, high volume machines specifically designed to shred large amounts of material daily. Ideally, they are placed in a common area and shared by employees.

Model	Strip width / particle size	Feed opening	Sheet capacity ¹	Security level	Shredding capabilities (non-paper)	Shred speed, ft. / min	Shred volume, gallons	Electrical requirements, volts	Maximum horsepower	Automatic oil injection / SSC ² / ECC ³	Dimensions (D x W x H)	Shipping weight
2503 strip-cut	.817" (4 mm)	10.25"	19-21	P-2		24	20	115	.75 (.58 kw)	-	14 3/4 x 19 3/4 x 34 1/4	78 lbs.
2503 cross-cut	.817" x 1.5" (4 x 40 mm)	10.25"	12-14	P-4		24	20	115	.75 (.58 kw)	-	14 3/4 x 19 3/4 x 34 1/4	78 lbs.
2503 cross-cut	.093" x .625" (2 x 15 mm)	10.25"	8-10	P-5		24	20	115	.75 (.58 kw)	-	14 3/4 x 19 3/4 x 34 1/4	78 lbs.
2604 strip-cut	.817" (4 mm)	10.25"	27-30	P-2		18	26	115	1 (.64 kw)	ECC	18 1/2 x 19 1/2 x 36 1/2	123 lbs.
2604 cross-cut	.817" x 1.5" (4 x 40 mm)	10.25"	23-25	P-4		18	26	115	1 (.64 kw)	ECC & auto oil	18 1/2 x 19 1/2 x 36 1/2	123 lbs.
2604 cross-cut	.093" x .625" (2 x 15 mm)	10.25"	14-16	P-5		18	26	115	1 (.64 kw)	ECC & auto oil	18 1/2 x 19 1/2 x 36 1/2	123 lbs.
2604 super micro-cut	.031" x .187" (.8 x 5 mm)	10.25"	6-8	P-7	-	28	26	115	1 (.64 kw)	ECC & auto oil	18 1/2 x 19 1/2 x 36 1/2	123 lbs.
3104 strip-cut	.817" (4 mm)	12"	27-30	P-2		18	32	115	1 (.64 kw)	ECC	18 1/2 x 21 x 36 1/2	132 lbs.
3104 cross-cut	.817" x 1.5" (4 x 40 mm)	12"	22-25	P-4		18	32	115	1 (.64 kw)	ECC	18 1/2 x 21 x 36 1/2	132 lbs.
3104 cross-cut	.093" x .625" (2 x 15 mm)	12"	14-17	P-5		18	32	115	1 (.64 kw)	ECC	18 1/2 x 21 x 36 1/2	132 lbs.
3105 cross-cut	.817" x 1.5" (4 x 40 mm)	12"	37-39	P-4		30	37	115 ⁴	2.1 (1.6 kw)	ECC & auto oil	23 x 22 x 40	324 lbs.
3105 cross-cut	.093" x .625" (2 x 15 mm)	12"	24-26	P-5		30	37	115 ⁴	2.1 (1.6 kw)	ECC & auto oil	23 x 22 x 40	324 lbs.
3804 cross-cut	.817" x 1.5" (4 x 40 mm)	16"	24-26	P-4		20	44	115	1 (.64 kw)	ECC	23.2" x 25.2" x 38.2"	233 lbs.
3804 cross-cut	.093" x .625" (2 x 15 mm)	16"	12-14	P-5		20	44	115	1 (.64 kw)	ECC	23.2" x 25.2" x 38.2"	233 lbs.
4001 cross-cut	.817" x 1.5" (4 x 40 mm)	16"	24-28	P-4		20	44	115	1 (.64 kw)	ECC	21.6" x 25.2" x 37.2"	174 lbs.
4001 cross-cut	.093" x .625" (2 x 15 mm)	16"	13-16	P-5		20	44	115	1 (.64 kw)	ECC	23.6" x 25.2" x 37.2"	174 lbs.
4002 strip-cut	.25" (6 mm)	16"	32-35	P-2		30	44	115	1.7 (1.3 kw)	ECC	23.2" x 25.2" x 38.2"	239 lbs.
4002 cross-cut	.093" x .625" (2 x 15 mm)	16"	14-16	P-5		25	44	115	1.7 (1.3 kw)	ECC & auto oil	23.2" x 25.2" x 38.2"	240 lbs.
4003 strip-cut	.25" (6 mm)	16"	43-45	P-2		30	44	115	1.7 (1.3 kw)	ECC	21.6" x 25.2" x 37.2"	166 lbs.
4003 cross-cut	.817" x 1.5" (4 x 40 mm)	16"	34-36	P-4		25	44	115	1.7 (1.3 kw)	ECC & auto oil	21.6" x 25.2" x 37.2"	179 lbs.
4003 cross-cut	.093" x .625" (2 x 15 mm)	16"	16-18	P-5		25	44	115	1.7 (1.3 kw)	ECC & auto oil	21.6" x 25.2" x 37.2"	179 lbs.
4003 super micro-cut	.031" x .817" (.8 x 5 mm)	16"	8-9	P-7	-	25	44	115	1.7 (1.3 kw)	ECC & auto oil	21.6" x 25.2" x 37.2"	179 lbs.
4005 strip-cut	.25" (6 mm)	16"	50-52	P-2		40	44	115 ⁴	2.1 (1.6 kw)	ECC & auto oil	23.2" x 25.2" x 39.7"	343 lbs.
4005 cross-cut	.817" x 1.5" (4 x 40 mm)	16"	37-39	P-4		30	44	115 ⁴	2.1 (1.6 kw)	ECC & auto oil	23.2" x 25.2" x 39.7"	378 lbs.
4005 cross-cut	.093" x .625" (2 x 15 mm)	16"	24-26	P-5		30	44	115 ⁴	2.1 (1.6 kw)	ECC & auto oil	23.2" x 25.2" x 39.7"	378 lbs.
4005 super micro-cut	.031" x .817" (.8 x 5 mm)	16"	10-12	P-7	-	44	44	115 ⁴	2.1 (1.6 kw)	ECC & auto oil	23.2" x 25.2" x 39.7"	390 lbs.

HIGH CAPACITY

A High Capacity in-house shredding program designed around Destroyit is the most secure and economical way of efficiently disposing large amounts of sensitive documents.

Model	Strip width / particle size	Feed opening	Sheet capacity ¹	Security level	Shredding capabilities (non-paper)	Shred speed, ft. / min.	Shred volume, gallons	Electrical requirements, volts	Maximum horsepower	Centralized oil injection	Dimensions (D x W x H), inches	Shipping weight
4606 cross-cut	.25" x 2" (6 x 50 mm)	18"	50-60	P-3		40	61	220, 3 phase	7.3 (2.2 kw)	P	30" x 29" x 67"	715lbs.
4606 cross-cut	.09" x .62" (2 x 15 mm)	18"	32-37	P-5		40	61	220, 3 phase	7.3 (2.2 kw)	P	30" x 29" x 67"	715 lbs.
4108 strip-cut	.25" (6 mm)	16"	75-95	P-2		60	79	220, 3 phase	10 (4 kw)	P	67" x 48.7" x 56.7" ⁵	994 lbs.
4108 cross-cut	.25" x 2" (6 x 50 mm)	16"	65-82	P-3		53	79	220, 3 phase	8 (3 kw)	P	67" x 48.7" x 56.7" ⁵	983 lbs.
5009 cross-cut	.34" x 1.5"-3" (8 x 40-80 mm)	20"	600-700	P-2		24-46 ⁶	79	220, 3 phase ⁷	24 (9 kw)	P	85.5" x 40.7" x 67.5" ⁸	3,080 lbs.
5009 cross-cut	.25" x 2" (6 x 50 mm)	20"	300-400	P-3		24-45 ⁵	79	220, 3 phase ⁷	24 (9 kw)	P	85.5" x 40.7" x 67.5" ⁸	3,080lbs.

LEGEND

¹ certified using 8.5" x 11" 20 lb. bond and recommended power supply

² SSC (Smart Shred Control) a smiley face illuminates to indicate adequate sheet capacity levels during shredding process

³ ECC (Electronic Capacity Control) prevents paper jams by monitoring sheet capacity levels during shredding process

⁴ 20 amp. dedicated line required

⁵ transportation width (minus side tables) is 2"

⁶ 2 automatic speed modes

⁷ 50 amp. dedicated line required

⁸ depth with modular conveyor belt system is 121"

- Paper clips / staples
- Plastic credit cards
- CDs / DVDs
- 3-ring binders

HIGH CAPACITY



DESKSIDE



CENTRALIZED OFFICE



WARRANTY

DESKSIDE & CENTRALIZED OFFICE SC & CC MODELS:

- lifetime limited warranty on cutting shafts and wheels
- 3-year limited warranty on all other parts, excluding wearables
- 90-day limited warranty on labor or exchange at MBM's discretion



HIGH CAPACITY AND SMC MODELS:

- 1-year limited warranty on cutting shafts and wheels
- 1-year limited warranty on all other parts, excluding wearables

SPECIAL SOLUTIONS MODELS:

- 1-year limited warranty, excluding wearables

Shown in actual size according to DIN 66399 (standard for the destruction of data).



MBM

3134 Industry Drive
North Charleston, SC 29418
843-552-2700
www.mbmcorp.com



IDEAL.MBM

945B Southgate Drive
Guelph, ON N1L 0B9
800-387-2528
www.ideal-mbm.com

DESTROYIT.

All technical data is approximate and subject to change. © MBM Corporation, 9/2024