DESTROYIT 4005

Our most powerful Centralized Office shredder comes with an automatic oiler in the micro-cut security level.

- A SOLID STEEL CUTTING SHAFTS
 High grade, hardened steel cutting shafts are milled in our Balingen factory.
- B ECC CAPACITY INDICATOR
 Patented Electronic Capacity Control
 (ECC) indicator monitors sheet capacity
 levels during operation to prevent jams.
- Multifunction control element uses optical signals to indicate the operational status, and functions as an emergency stop switch.
- Durable, lightweight shred bins can be used with or without disposable bags.



^{*}Micro-cut shafts are covered by a 1 year warranty.

DESTROYIT 4005

Comprehensive SPS safety package: Easy Switch control element uses illuminated color codes and symbols to indicate operational status and functions as an emergency stop switch; patented, electronically controlled, transparent safety shield in the feed opening; automatic power cut-off when cabinet is opened or shred bin is full; automatic reverse and power cut-off when overfed; double protection against overheating; Zero Energy Consumption sleep mode cuts off power supply after 30 minutes of inactivity.

Automatic start and stop controlled by photo cell. Automatic oil injection ensures optimal performance at all times. High quality, hardened steel cutting shafts. Micro-cut model meets all NSA/CSS specifications and is DOD approved. Quiet and powerful single phase motor rated for continuous operation. Sturdy chain drive with fully enclosed gear box housing. High quality wooden cabinet mounted on casters.

Security level P-6	.1/32" x 15/32" micro-cut
Sheet capacity	17 - 21*

*Sheet Capacity is based on 70 gsm paper, and are normally only achievable in ideal situations, so heavier duty paper will shred less sheets. In many cases the capacities quoted are theoretical as conditions vary and are dependent on operator usage, age and condition of machines, how regularly cutters are oiled, type and quality of paper etc. so realistic throughputs can be as low as half that of the theoretical capacities quoted.

Specifications:

Shred volume	44 gallons
Feed opening	16"
Electrical requirements	115 volts ¹
Maximum horsepower	2.12
Dimensions (D x W x H)	23.25" x 25.25" x 39.75"
Shipping weight	343 (sc), 378 (cc), 390 (smc)
-	

¹20 amp. dedicated line required.





